



- **20.4% efficiency**


Ideal for roofs where space is at a premium or where future expansion might be needed.

- **High performance**

Delivers excellent performance in real world conditions, such as high temperatures, cold and low light.^{1, 2, 3}

- **Proven value**

Designed for residential rooftops, E-Series panels deliver the features, value and performance for any home.



Moxeon® Solar Cells: Fundamentally better.

Engineered for performance, designed for durability.

Engineered for peace of mind


Designed to deliver consistent, trouble-free energy over a very long lifetime.^{4, 5}

Designed for durability

The SunPower® Moxeon® Solar Cell is the only cell built on a solid copper foundation. Virtually impervious to the corrosion and cracking that degrade Conventional Panels.^{4, 5}

#1 Ranked in Fraunhofer durability test.¹⁰
100% power maintained in Atlas 25+ comprehensive PVDI Durability test.¹¹

HIGH PERFORMANCE & EXCELLENT DURABILITY



E20 - 327 PANEL



HIGH EFFICIENCY⁶



Generate more energy per square foot

E-Series residential panels convert more sunlight to electricity producing 36% more power per panel,¹ and 60% more energy per square foot over 25 years.^{3, 4}

HIGH ENERGY PRODUCTION⁷


Produce more energy per rated watt

High year one performance delivers 7-9% more energy per rated watt.³ This advantage increases over time, producing 20% more energy over the first 25 years to meet your needs.⁴




SUNPOWER OFFERS THE BEST COMBINED POWER AND PRODUCT WARRANTY

POWER WARRANTY



More guaranteed power: 95% for first 5 years, -0.4%/yr. to year 25. ⁸

PRODUCT WARRANTY



Combined Power and Product Defect 25 year coverage that includes panel replacement costs. ⁹

ELECTRICAL DATA

| | E20-327 | E19-320 |
|---|-----------------------|----------------|
| Nominal Power ¹² (P _{nom}) | 327 W | 320 W |
| Power Tolerance | +5/-0% | +5/-0% |
| Avg. Panel Efficiency ¹³ | 20.4% | 19.8% |
| Rated Voltage (V _{mpp}) | 54.7 V | 54.7 V |
| Rated Current (I _{mpp}) | 5.98 A | 5.86 A |
| Open-Circuit Voltage (V _{oc}) | 64.9 V | 64.8 V |
| Short-Circuit Current (I _{sc}) | 6.46 A | 6.24 A |
| Maximum System Voltage | 600 V UL ; 1000 V IEC | |
| Maximum Series Fuse | 20 A | |
| Power Temp Coef. (P _{mpp}) | -0.38% / °C | |
| Voltage Temp Coef. (V _{oc}) | -176.6 mV / °C | |
| Current Temp Coef. (I _{sc}) | 3.5 mA / °C | |

OPERATING CONDITION AND MECHANICAL DATA


| | |
|-------------------|---|
| Temperature | - 40°F to +185°F (- 40°C to +85°C) |
| Max load | Wind: 50 psf, 2400 Pa, 245 kg/m ² front & back Snow: 112 psf, 5400 Pa, 550kg/m ² front |
| Impact resistance | 1 inch (25 mm) diameter hail at 52 mph (23 m/s) |
| Appearance | Class A |
| Solar Cells | 96 Monocrystalline Maxeon Gen II Cells |
| Tempered Glass | High Transmission Tempered Anti-Reflective |
| Junction Box | IP-65 Rated |
| Connectors | MC4 Compatible |
| Frame | Class 1 black anodized, highest AAMA Rating |
| Weight | 41 lbs (18.6 kg) |

TESTS AND CERTIFICATIONS

| | |
|--------------------|---|
| Standard tests | UL 1703, IEC 61215, IEC 61730 |
| Quality tests | ISO 9001:2008, ISO 14001:2004 |
| EHS Compliance | RoHS, OHSAS 18001:2007, lead-free |
| Ammonia test | IEC 62716 |
| Salt Spray test | IEC 61701 (passed maximum severity) |
| PID test | Potential-Induced Degradation free: 1000V ¹⁰ |
| Available listings | CEC, JET, KEMCO, MCS, FSEC, CSA, UL, TUV |

REFERENCES:

- 1 All comparisons are SPR-E20-327 vs. a representative conventional panel: 240W, approx. 1.6 m², 15% efficiency.
- 2 PVEvolution Labs "SunPower Shading Study," Feb 2013.
- 3 Typically 7-9% more energy per watt, BEW/DNV Engineering "SunPower Yield Report," Jan 2013.
- 4 SunPower 0.25%/yr degradation vs. 1.0%/yr conv. panel. Campeau, Z. et al. "SunPower Module Degradation Rate," SunPower white paper, Feb 2013; Jordan, Dirk "SunPower Test Report," NREL, Oct 2012.
- 5 "SunPower Module 40-Year Useful Life" SunPower white paper, Feb 2013. Useful life is 99 out of 100 panels operating at more than 70% of rated power.
- 6 Out of all 2600 panels listed in Photon International, Feb 2012.
- 7 8% more energy than the average of the top 10 panel companies tested in 2012 (151 panels, 102 companies), Photon International, March 2013.
- 8 Compared with the top 15 manufacturers. SunPower Warranty Review, Feb 2013.
- 9 Some exclusions apply. See warranty for details.
- 10 5 of top 8 panel manufacturers were tested by Fraunhofer ISE, "PV Module Durability Initiative Public Report," Feb 2013.
- 11 Compared with the non-stress-tested control panel. Atlas 25+ Durability test report, Feb 2013.
- 12 Standard Test Conditions (1000 W/m² irradiance, AM 1.5, 25° C).
- 13 Based on average of measured power values during production.



See <http://www.sunpowercorp.com/facts> for more reference information.

For further details, see extended datasheet: www.sunpowercorp.com/datasheets Read safety and installation instructions before using this product.

Designed in California
sunpowercorp.com

© March 2013 SunPower Corporation. All rights reserved. SUNPOWER, the SUNPOWER logo, MAXEON, MORE ENERGY. FOR LIFE., and SIGNATURE are trademarks or registered trademarks of SunPower Corporation. Specifications included in this datasheet are subject to change without notice.

Document # 504860 Rev A /LTR_EN